Copy 4 CL-115232

Doc. No. MS128W0002 31 DECEMBER 1970

NASA APPROVED

DATA BOOK SPACE STATION/BASE FOOD SYSTEM STUDY **BOOK III** STUDY SELECTION RATIONALE SHEETS

Prepared for

NATIONAL AERONAUTICS and SPACE ADMINISTRATION

Manned Spacecraft Center Houston, Texas 77058

> TECHNICAL LIBRARY **BUILDING 45**

> > FEB 2 6 1971

Contract NAS9-11139 DRL Line Item No.12

lanned Spacecraft Center Youston, Texas 77058

OFFICE OF PRIME RESPONSIBILITY



Prepared by Manned Space Systems

FAIRCHILD REPUBLIC DIVISION

(NASA-CR-115232) DATA BOOK: STATION/BASE FOOD SYSTEM STUDY. BOOK 3: STUDY SELECTION RATIONALE SHEETS (Fairchild Hiller Corp.) 31 Dec. 1970

NATIONAL TECHNICAL INFORMATION SERVICE Springfield, Va. 22151

DEC 197

G3/05

Unclas 09504

DATA BOOK SPACE STATION/BASE FOOD SYSTEM STUDY BOOK III STUDY SELECTION RATIONALE SHEETS

Prepared for

NATIONAL AERONAUTICS and SPACE ADMINISTRATION

Manned Spacecraft Center Houston, Texas 77058

Contract NAS9-11139 DRL Line Item No.12

Prepared by Manned Space Systems



CONTENTS

Section		Page
	Abstract	iii
I	INTRODUCTION AND SUMMARY	1
п	SELECTION RATIONALE	2
	A. System	2
	B. Form and Instruction	2
	C. Rationale Sheets · · · · · · · · · · · · · · · · · · ·	2
	Functional Subsystem Area 1.0 Provide For Food · · · · · · · · · · · · · · · · · ·	7
	Functional Subsystem Area 2.0 Provide For Storage of Food · · · · · · · · · · · · · · · · · ·	36
	Functional Subsystem Area 3.0 Provide For Preparation of Food · · · · · · · · · · · · · · · · · ·	55
	Functional Subsystem Area 4.0 Provide For Serving of Food	113
	Functional Subsystem Area 5.0 Provide For Consumption of Food · · · · · · · · · · · · · · · · · ·	121
	Functional Subsystem Area 6.0 Provide For Clean-Up of Food	154
	Functional Subsystem Area 7.0 Provide For Recording of Food	191

ABSTRACT

The Fairchild Hiller Corporation, Republic Aviation Division, performed a seven-month study under Contract Number NAS9-11139 entitled "Space Station/Base Food System Study" for the National Aeronautics and Space Administration, Manned Spacecraft Center. The study was conducted so as to identify and define engineering data for a spectrum of possible items and equipment comprising potential food systems for use on manned spacecraft and assemble these data in a Final Report and Data Book.

This document is Book III of the Data Book. The Data Book, containing the detailed technical data, supporting analysis, and selection rationale for each of the concepts considered in the Final study, has been prepared in three books:

Book I - Element Concept Data Sheets

en grande de la companya de la compa

This book contains the detail engineering data sheets for all concepts studied in the Final phase of the contract effort as well as those concept sheets only carried through the Interim phase due to non-applicability or deleted missions.

Book II - Supporting Technical Data

This book contains formulae, assumptions, calculations, and supporting analyses for the element concept data sheets.

Book III - Study Selection Rationale Sheets

This book contains the supporting rationale sheets utilized in selection and support of those concepts studied in the Final phase of the contract.

The results of the study have been compiled in the Final Report - Volumes I and II, which contain the documentation and summary of the contract effort.

The program was performed under the technical direction of Mr. Dean Glenn, Habitability Technology/Spacecraft Design Office of the Manned Spacecraft Center.

SECTION I

INTRODUCTION AND SUMMARY

The study selection rationale sheets support the concept study/discard decisions reached at the conclusion of the Interim phase of the contract effort. Each concept, conceived to fulfill a specific function of the food system, was assessed in terms of the eight critical factors depicted on the rationale sheet. When weighted and totaled, the resulting selection factor was used as a guide in making the final decision. In certain cases, engineering judgment was used to override a number and continue or discard a concept in the Final study. The selection rationale should be utilized primarily as a tool to assist the designer in assessing the overall validity of a concept and should not be considered as the ultimate test for the worth of the concept.

SECTION II

SELECTION RATIONALE

A. SYSTEM

Each concept conceived to satisfy the requirements of the primary functional areas comprising a food system was evaluated during the Initial and Interim study for possible detailed study in the Final phase of the contract effort. The concepts were numbered in accordance with their functional area, and then analyzed utilizing a quantitative evaluation and selection rationale. If the concept met the acceptance criteria rating of 9.0 or better, it was selected for more detail study during the Final phase, unless some overriding consideration dictated no further study.

B. FORM AND INSTRUCTION

Figure II-1 is a copy of the Concept Selection Rationale Sheet utilized and the instructions for its use.

C. RATIONALE SHEETS

The selection rationale sheets are presented herein by functional area and provide a complete listing of all researched and original concepts conceived during the course of the study. No constraints were imposed on the study group personnel in developing original concepts other than reasonable mechanical and physical feasibility. Each concept is described in detail and a technical analysis rationale provided in Volume I of the Final Report. The rationale for any overriding decisions is also explained in the technical analysis. As an example, for Concept 1.1.18 - Crewman Modification, the selection factor was 10.2, which would indicate further study. In the technical analysis rationale of Volume I - Final Report, a description of this concept indicates the reasons for discarding it from further study. Finally, it should be noted that no selection rationale sheets were prepared for Functional Subsystem Area 7.0 - Provide For Recording of Food, due to the joint NASA/Contractor decision to study overall requirements rather than specific equipment concepts. These requirements are reviewed in detail in Final Report, Volume I, Section III, paragraph 7.0.

Concept	No.	SELECTION RATIONALE			tor	**
Title		Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	\(\) Mult x Factor	Chart Use
1	Gravitational Factor	Station G O Factor Station G Station G	3	 		
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	<u> </u> 		
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2			
4	Crew Size Acceptability Factor	The second of th	1			
5	Development Risk Factor	Crew Acceptability Excellent Good Fair Foor (hazardous) Safety O	3	 		
6	Operability Factor	X 2 1 1 0 Complex Simple	1			
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2			
8	System Compatibility Factor	3 1.8 1.5 X 1.0 X 1.0 Weight Low High Low High Low Weight X Power X Volume	4			
	FINAL SELE	CTION FACTOR = (Mult x Factor) Number of Charts Used			Sun	Sum
	INTERIM STUD	Y SELECTION: DISCARD or STUDY				

Figure II-1. Concept Selection Rationale Sheet

INSTRUCTIONS: CONCEPT SELECTION RATIONALE SHEET

A quantitative rationale was established in order to document the selection for further study of the various concepts listed for each functional food category; i.e., provide, serve, consume food, etc. The rationale considers the following parameters, all or part of which affect the stated concepts to some extent:

- 1) <u>Gravitational Effect</u>: This parameter is employed to consider the gravitational effect on a particular concept for a range of station operability between zero-g to one-g.
- 2) Crew Acceptability: This is a measure of the anticipated crew acceptability for a concept; the rating ranges from excellent, to good, fair, poor, and not acceptable. As applicable, crew acceptability criteria is considered for such elements as: sensory input (sight, smell, etc.); familiarity; task complexity, meniality, or boredom; esthetics; and confidence.
- 3) Safety: A measure of the condition (of the particular item or concept) of being safe from causing hurt, injury, loss, or inactivity. The rating ranges from excellent, to good, fair, and poor or hazardous.
- 4) <u>Crew Size Applicability</u>: A measure of the effect of crew size, ranging to a station complement of 50 on the particular item or concept. This parameter considers the effect based on quantity; a concept, for instance, considered for a six-man station may be more (or less) effective than such a concept for a fifty-man station.
- Development Risk: This parameter considers the status of a particular concept and ranges from what is available or current state-of-the-art, to various magnitudes of effort required to fully develop the concept for space station usage. Since concept complexity, development time, and required development funding are closely related, the parameter has been established from a consideration of one of these; namely, development time. The time period from the present to the anticipated station availability of 1978, or a development period covering eight years, has been used.
- 6) Operability: This parameter pertains to the product of two factors related to the reliability and maintainability of the particular concept. Reliability is scaled from a low to high ranking, and maintainability is assumed to range from complex to simple maintenance task requirements.
- 7) Crew Time: A measure of crew time requirements for a particular concept, ranging from maximum to minimum. The scale ranges from minimal time requirements through low, medium, and high usage of crew time to accomplish a functional task.

8) System Compatibility: This parameter pertains to the product of three prime systems considerations; namely, the weight, volume, and power requirements for each concept under consideration. The effect of weight is considered twice that of volume since the launch weight of the station (and/or resupply weight) is considered to govern, rather than the volumetric constraint of the station. Since power requirements are more closely related to weight, than are volume requirements for the station, this subparameter of the system compatibility factor has been assumed of 20% greater importance than volume.


In order to normalize the eight parameters, the following multipliers (or effective weights) have been established. The list, for example, shows that "System Compatibility" is considered to have twice the impact on selection as "Crew Time".

	Parameter	Multiplier
1)	Gravitational Effect	3
2)	Crew Acceptability	3
3)	Safety	2
4)	Crew Size	1
5)	Development Risk	3
6)	Operability	1
7)	Crew Time	2
8)	System Compatibility	4

It is to be noted that although Safety may appear to be ranked too low, thus of not sufficient emphasis, this parameter primarily reflects the relative ranking prior to the final selection of a concept. Once a concept is selected for space station use it most certainly must evolve to be as safe as possible; prior to that, however, the weighting of safety must be considered in light of all other parameters. More development or crew time, for instance, could readily turn a poor safety item into one exhibiting excellent safety characteristics.


Graphs, presenting the particular criteria for each parameter, have been produced to establish a set of factors which are employed in the concept selection process. The factors for each parameter range, in general, from zero to a value of eight. For the two parameters in which products are used (Operability and System Compatibility), the use of more readily scaled numbers produces maximum values slightly in excess of eight. The summation of the product of all factors and their appropriate multipliers gives an overall sum, which when divided by the number of parameters utilized in the process, yields the "final selection factor". This factor is then compared to a preselected value; a final selection factor below this value means that the concept is discarded, a factor equal to or above the selected value implies that the concept has been selected for further study.

The format for the concept selection rationale is shown in the attached figure. It is to be noted that three basic types of graphs are employed; their use is clarified in the following paragraphs, taking an example of each type:




Example: Examine the concept of drinking liquid from a standard cup, considering the effect of gravitational forces.

First, from an examination of the charts at point g=0, it is determined that the left hand graph is applicable since for a non-spinning station (zero-g) the concept is low on the effectivity scale at that point. Secondly, mentally construct the shape of a curve (see dotted line) which best represents the anticipated effectivity of the concept as g-forces increase. Since the curve falls within area 2, a factor of 2 is recorded in the appropriate column of the chart.



Example: Examine the concept of drinking liquid from a standard cup, considering the effect of crew acceptability.

The graph shows a linear relationship between crew acceptability and rating factor, and gives the investigator a choice of two ways to obtain the factor. In the first case, if one anticipates that 3 out of 6 crew members (50%) could find the concept acceptable (as opposed to unacceptable), then a factor of 4 is obtained. The more standard way would be to consider how the average crew member would view the concept, a ranking of 'poor' would at its highest range also yield a factor of 4. The poor rating for this concept is based on the fact that although a drinking cup is standard for terrestrial use, it must be considered (1) in light of the overall station usage (which is oriented primarily towards zero-g applicability), and (2) in comparison with other recommended concepts for this task.




This graph shows a linear relationship between reliability and the rating factor. Since this and other graphs of this type are employed where the product of two or more chart factors are taken, discrete points are established between (in this case) low and high ratings, in order to simplify the procedure. A low rating gives a factor of either 0 or 1; a high rating 2 or 3; and an intermediate reliability rating of either 1 or 2.

Figure II-1. Concept Selection Rationale (concluded)


FUNCTIONAL SUBSYSTEM AREA 1.0


PROVIDE FOR FOOD





Concept No	. 1.1.2	SELECTION RATIONALE			actor	**
Title: FROZEN UNPROCESSED		Select appropriate curve representation, then use corresponding factor, * Estimate shape of curve and use the corresponding section number into which the curve falls, ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	Mult x Factor	Chart Use
1 (Gravitational Factor	Station G Factor Station G Station G	3	0	0	0
2 A	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	7	21	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 <i>5</i> 	10	1
	Crew Size Acceptability Factor	Crew Number	1	6	6	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 7 	21	1
6	Operability Factor	3 3 3 X 2 1 0 X 2 1 0 Complex Simple Reliability X Maintainability	1	2	2	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	2	2	1
8 (System Compatibility Factor	3 1.8 1.5 X 1.0 X	4	 1.8 	7. Z	1
	FINAL SELECTION	ACTOR (9.8) = (Mult x Factor) 69.2			Sum	Sun
	FINAL SELECTION	ACTOR (9.8) = (Mult x Factor) 69.2 - 7			Sum	


Concept No. / . /. 3	SELECTION RATIONALE			ctor	**
Title: FROZEN PROCESSE	Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	\(\race{\cap Mult x Factor} \)	Chart Use
l Gravitational Factor	Station G Pactor Supering Station G Pactor Station G Station G	3	0	o	0
2 Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	7	21	1
3 Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	5	10	1
4 Crew Size Acceptability Factor	Too of the second secon	1	 8	8	1
5 Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 7 	21	1
6 Operability Factor	X 2 1 1 1 1 1 1 1 1 1 1 1 1 1	1	 2 	2	1
7 Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	8	16	1
8 System Compatibility Factor	X 1.8 1.5 X 1.0 X 1.0 High Low High Low Weight X Power X Volume	4	1.2	4.8	1
FINAL SELECTION	FACTOR //-8 = $\frac{\sum (\text{Mult x Factor})}{\text{Number of Charts Used}}$ = 7			Sum	Sui
INTERIM STUDY SELEC	CTION: DISCARD or STUDY \(\left(\sigma \text{9} \) \(\left(\sigma \text{9} \)				














SELECTION RATIONALE Mult x Factor Concept No. 1. 1. 9 Select appropriate curve representation, then use corresponding factor. Use Multiplier * Estimate shape of curve and use the corresponding section number Factor Chart DEHYDROFROZEN into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. O Factor Concept Effectiveness **®** Ø⁄2 7 **④ ®** 1 Gravitational 3 0 0 6 0 Factor Station G Station G Excellent Factor ~Good Fair 18 2 6 Crew 3 Poor Acceptability 1 Factor Crew Acceptability Excellent Factor Good 2 6 12 Safety 3 Fair 1 Factor Poor (hazardous) 100% Safety Concept Effectiveness (8) 1009 Ø Ø 6 Crew Size 1 6 4 (5) 1 Acceptability Factor Crew Number Crew Number Available or current state of the art Factor Some development required - Broad development required 5 Development 3 18 6 -Major development required 1 Risk or not feasible (1978)Factor Development Time, \$, or Complexity Factor 2 X 2 2 Operability 1 6 1 Factor 0 Complex X Maintainability Reliability -Minimal amount of crew time Factor – Low – Medium 2 5 10 7 Crew Time -High Factor 1 Min. Max Crew Time Factor 1.2 8 System 4 1.6 6.4 0 1 Compatibility High Low High Low High Low Factor Weight x Power X Volume Sum (Mult x Factor) 72.4 Sum FINAL SELECTION FACTOR 10.3 Number of Charts Used 7 INTERIM STUDY SELECTION: YQUTS DISCARD (≤ 9)


FAIRCHILD HILLER








FAIRCHILD HILLER

































Concept No. 1.2.4	SELECTION RATIONALE		T I	actor	*
Title: EDIBLE PAG	Select appropriate curve representation, then use corresponding factors to the stimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in	1 🏗	Factor	Mult x Factor	Chart IIsa
l Gravitational Factor	Station G O Far	3	0	0	,
2 Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	 0 	0	
3 Safety Factor	Excellent Good Fair Poor (hazardous)	2	1	2	
4 Crew Size Acceptability Factor	100% 8 10	1	0	0	
5 Development Risk Factor	Available or current state of the arrest state	3	5	15	
6 Operability Factor	3 2 X 2 1 1 0 Complex Simple Reliability X Maintainability	1	2	2	
7 Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	7	14	
8 System Compatibility Factor	3 1.8 1.5 X 1.0 X	4	8	32	
FINAL SE	CTION FACTOR $(9.2) = \frac{\sum (Mult \times Factor)}{Number of Charts Used} = 7$			Sum	S
FINAL SE	CTION FACTOR (4.2) = Number of Charts Used 7	4			












SELECTION RATIONALE Concept No. 1. 2. 9 Mult x Factor Title: STORAGE | SERVICE Select appropriate curve representation, then use corresponding factor. Multiplier * Estimate shape of curve and use the corresponding section number into which the curve falls, Factor ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. Concept Effectiveness O Factor 7 **④ ®** 1 Gravitational 0 3 0 6 Factor 0 Station G Station G Excellent Factor Cood 2 Crew Fair 7 3 21 Acceptability 1 Factor Crew Acceptability Factor Excellent 14 Good 3 Safety 7 2 Fair Factor Poor (hazardous) 1 Safety Concept Effectiveness 1009 1009 Ø Ø Crew Size 1 4 1 1 (5) Acceptability 1 Factor Crew Number Crew Number -Available or current state -of-the-art Factor Some development required
Broad development required 5 Development 5 15 3 -Major development required Risk or not feasible (1978)1 Factor Development Time, \$, or Complexity 2 х 6 Operability 1 Factor Complex 1 Reliability X Maintainability -Minimal amount of crew time Factor - Low -Medium 7 2 7 Crew Time - High ő Factor 1 Min. Max Crew Time 1.8 1.5 Factor 8 System 1.3 1.2 Compatibility 1 Lou Low High High Low High Factor Weight X Power X Volume Sum 72.2 (Mult x Factor) Sum FINAL SELECTION FACTOR 10.3 Number of Charts Used 7 INTERIM STUDY SELECTION: STUDY [DISCARD




FUNCTIONAL SUBSYSTEM AREA 2.0


PROVIDE FOR STORAGE OF FOOD








SELECTION RATIONALE Mult x Factor Concept No. 2. 1. 3 Select appropriate curve representation, then use corresponding factor. Title CRYOGENIC EXPANSION * Estimate shape of curve and use the corresponding section number into which the curve falls. Factor Chart FREEZER ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. O Factor Concept Effectiveness **®** 0 **©** 4 Gravitational 1 3 12 **⑤** Factor 1 Station G Station G Excellent Factor -Good Fair 3 7 21 2 Crew Poor 1 Acceptability 100% Factor 50 Crew Acceptability Excellent Factor Good 2 1 2 Safety 3 Fair 1 Factor Poor (hazardous) Safety Concept Effectiveness 1000 1009 0 இ 2 2 1 Crew Size 4 ➂ Œ Acceptability 1 Factor Crew Number -Available or current state -of-the-art Factor Some development required Broad development required 3 4 12 Development 5 -Major development required 1 or not feasible Risk (1978) Factor Development Time, \$, or Complexity x 2 Factor 1 1 1 1 6 Operability Factor 1 Complex X Maintainability Reliability -Minimal amount of crew time Factor Low _ __Medium 2 0 0 7 Crew Time -High 1 0 Factor Max. Min Crew Time 1.5 Factor 1.2 1,0 4 | .9 System 8 3.6 0 Compatibility 1 High High Low High Low Factor Weight X Power 1.8 X Volume .5 (Mult x Factor) 53.6 Sum FINAL SELECTION FACTOR 7.45 Number of Charts Used INTERIM STUDY SELECTION: DISCARD 4 or
































Select appropriate curve representation, then use corresponding factor.	1			1
Estimate shape of curve and use the corresponding section number into which the curve falls. Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	\[\] Mult x Factor	1000
Station G OF Factor OF Station G Station G	3	4	12	
Excellent Good Fair Poor Crew Acceptability	3	7	21	
Excellent Good Fair Poor (hazardous) Safety	2	8	16	
Tabout 100% B 10	1	1	1	
Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	6	18	
X 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	 <u>4</u> 	4	
Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	0	0	
High Low High Low High Low Weight X Power X Volume 1	4	 -6 	2.4	
$\frac{10.6}{\text{CTOR}} = \frac{\sum_{\text{(Mult x Factor)}} \frac{74.4}{\text{Number of Charts Used}} = \frac{74.4}{7}$			Sum	5
	Station G Station G Station G Station G Station G Excellent Good Crew Acceptability Excellent Cood Fair Poor O Safety Available or current state-of-the-art Some development required Or not feasible Development Time S, or Complexity To The Reliability T	Station G Station Station Station Station Station Station Station Station Station Station Station Station Station Station St	Station G Station	Station G Station G








SELECTION RATIONALE Mult x Factor Concept No. 2.3.3 Select appropriate curve representation, then use corresponding factor. Title AMBIENT STORAGE * Estimate shape of curve and use the corresponding section number Factor Chart into which the curve falls. EXTRAVEHICULAR CONCEPT ** Chart use: If chart is used, put 1 in this column; if not used. put in 0. Concept Effectiveness 40001 O Factor ⑧ 7 **④** 1 21 1 Gravitational 3 7 (5) Factor 1 Station G Station G Excellent -Good Fair 1 3 2 Crew 3 Acceptability 1 Factor Crew Acceptability Excellent Good 2 2 1. Safety 3 Fair Factor Poor (hazardous) 100% 1 Safety Concept Effectiveness 1009 100% Ø Ø 2 2 1 Crew Size (3) Acceptability Factor 1 Crew Number Crew Number Available or current state-of-the-art Some development required

Broad development required Factor 5 15 Development 3 5 -Major development required Risk or not feasible (1978)Factor 1 Development Time, \$, or Complexity Х 2 1 Operability 6 Factor n 1 X Maintainability Reliability Minimal amount of crew time 2 2 1 Medium Crew Time 7 High Factor 1 Min. Max Crew Time 1.5 1.0 1.2 System 13.6 14.4 8 0. Compatibility 1 Low High Low High Low High Factor X Power 1. 6 X Volume 2 Weight Sum 42.4 Sum (Mult x Factor) FINAL SELECTION FACTOR 5.3 Number of Charts Used 8 DISCARD INTERIM STUDY SELECTION:


FUNCTIONAL SUBSYSTEM AREA 3.0


PROVIDE FOR PREPARATION OF FOOD





Concept No. 3.1. 2	2 .	SELECTION RATIONALE			i g	**
Title POWER SOURCE SOLAR INTERLOOP		Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls, ** Chart use: If chart is used, put in this column; if not used, put in 0.	Mumpher	Factor	Mult x Factor	Chart Use
l Gravitatio Factor	nal	Station G OF Factor Station G Station G	3	4	12	1
2 Crew Acceptabili Factor	ty	Excellent Good Fair Poor Crew Acceptability	3	4	12.	1
3 Safety Factor		Excellent Good Fair Poor (hazardous) Safety	 2 	6	12	1
4 Crew Sizo Acceptabili Factor		To be		2	2	1
5 Developme Risk Factor	ent	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3 3 1	5	15	1
6 Operabilit Factor	у	X 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		1	1	1
7 Crew Tim Factor	e	Minimal amount of crew time Low Medium High Max. Crew Time	·	Ø	0	
8 System Compatibil Factor	ity	1.8 X 1.2 X 1.0 X 1.0 X 1.0 X 1.0 Weight I X Power I.2 X Volume	 	0	0	1
FINA	L SELECTION FAC	CTOR 7.7 = $\frac{\sum_{\text{(Mult x Factor)}}{\text{Number of Charts Used}}$ = 7			Sum	Sum
INTERIM	STUDY SELECTIC	ON: DISCARD or STUDY (> 9)				






















FAIRCHILD HILLER
















SELECTION RATIONALE Concept No. 3. 2. 4 Title DIELECTRIC HEATING Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number Factor OVEN Chart 1 into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. O Factor Concept Effectiveness 7 **4 ®** Gravitational 3 (5) 8 24 Factor 1 Station G Station G Excellent Factor 2 Crew Fair 3 2 6 Poor Acceptability Factor 1 Crew Acceptability Excellent 3 Safety Good 2 5 10 Fair Factor Poor (hazardous) 100% Safety 1 Concept Effectiveness 0 4 Crew Size 1 1 1 Acceptability Factor 1 Crew Number Crew Number Available or current state-of-the-art Factor -Some development required - Broad development required -Major development required 5 Development 3 5 15 Risk or not feasible (1978)Factor 1 Development Time, \$, or Complexity Factor х Operability 6 2 2 1 Factor Complex 1 X Maintainability Reliability -Minimal amount of crew time – Low – Medium 2 7 Crew Time 3 n Factor Min. Crew Time 1 1.8 Factor 5 8 System 4 2 8 Compatibility 0 High High Factor 1 Weight X Power 2 X Volume Sum \sum (Mult x Factor) Sum 72 FINAL SELECTION FACTOR Number of Charts Used INTERIM STUDY SELECTION: DISCARD (≤ 9) **V**















Conce	ept No. 3. 2. 10	SELECTION RATIONALE			for	**
Title PRESSURE COOKER HEATING		Select appropriate curve representation, then use corresponding factor. • Estimate shape of curve and use the corresponding section number into which the curve falls, •* Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	\(\) Mult x Factor	Chart Use
1	Gravitational Factor	Station G Station G O Factor	3	4	12	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	2	6	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 2 	4	1
4	Crew Size Acceptability Factor	Crew Number Crew Number	1	 2 	2	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 4 	12	1
6	Operability Factor	3 X 2 1 1 0 Complex Simple Reliability 1 X Maintainability Z	1	1	2	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	4	8	1
8	System Compatibility Factor	3 1.8 1.5 X 1.0 X Y 1.0 X Y 1.0 X Y 1.0 X Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y	4	 1 	4	1
	FINAL SELEC	TION FACTOR 6.3 = \frac{\sqrt{(Mult x Factor)}}{\text{Number of Charts Used}} = \frac{50}{6}			Sum	Sum
	INTERIM STUDY					










FAIRCHILD HILLER












oncept No. 3.4·3	SELECTION RATIONALE		 	actor	**
itle FOLD - AWAY REPARATION COUNTER	Select appropriate curve representation, then use corresponding factor. • Estimate shape of curve and use the corresponding section number into which the curve falls, •• Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	Mult x Factor	Chart Use
1 Gravitational Factor	Station G Pactor Factor Station G Station G	3	2	Q	
2 Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	4	12	
3 Safety Factor	Excellent Good Fair Poor (hazardous)	2	 2 	4	
1 Crew Size Acceptability Factor	Crew Number Crew Number	1	 4 	4	
5 Development Risk Factor	Available or current state of the art Some development required Broad development required Broad development required Or not feasible Development Time, \$, or Complexity	3	 8 	24	
6 Operability Factor	X 2 1 1 0 Now High Complex Simple Reliability X Maintainability	1	 4 	4	
7 Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	 4 	8	
8 System Compatibility Factor	1.8 1.5 X 1.0 X 1.0 X 1.0	4	 8.1 	32.4	1
FINAL SELECTION FAC	CTOR 11.8 = $\frac{\sum (\text{Mult x Factor})}{\text{Number of Charts Used}}$ = $\frac{94.4}{8}$			Sum	Sur








SELECTION RATIONALE Mult x Factor Concept No. 3.5.1 Use Select appropriate curve representation, then use corresponding factor. SNACK BAR Title * Estimate shape of curve and use the corresponding section number into which the curve falls. Chart ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. Concept Effectiveness (8) **4 %** \bigcirc **©** Gravitational 5 15 3 (3) Factor 1 Station G Station G Excellent 2 Fair 3 8 24 Crew Poor Acceptability Factor 50 1 Crew Acceptability Excellent Good 8 2 4 3 Safety Fair Factor Poor (hazardous) 1 Safety Concept Effectiveness 100% 100% Ø Ø, Crew Size 4 (5) Acceptability 0 Factor 1 Crew Number Crew Number Available or current state-of-the-art Some development required Broad development required 12 3 5 Development Major development required or not feasible Risk Factor Development Time, 1 \$, or Complexity х 1 1 1 Operability Factor Complex 1 X Maintainability Reliability -Minimal amount of crew time - Low Medium 6 12 Crew Time High ሰ Factor Max. Min. Crew Time 1 1.5 1,2 2.4 System 4 8 Compatibility Low Low High High Low High Factor Weight X Power 1.2 X Volume .5 Sum 78.4 \sum (Mult x Factor) Sum FINAL SELECTION FACTOR 9.8 Number of Charts Used 8 INTERIM STUDY SELECTION: DISCARD


Conce	pt No. 3.6.1	SELECTION RATIONALE	ļ	Ţ	rot	**
Title FOOD DISPENSER CABINET		Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls, ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	\(\rangle \) Mult x Factor	Chart Use
1	Gravitational Factor	Station G OF Factor Station G Station G	3	7	21	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	4	12	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 4 	8	1
4	Crew Size Acceptability Factor	The second secon	1	6	O	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 8 	24	1
6	Operability Factor	Section 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	4	4	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	4	8	1
8	System Compatibility Factor	1.8 1.5 X 1.0 X	4	1.2	4.8	1
	FINAL SELEC	TION FACTOR 10.9 = \(\sum_{\text{Number of Charts Used}} \) = \(\text{87.8} \)			Sum	Sum
	INTER IM STUDY	Number of Charts Osed 8		<u> </u>		_















FAIRCHILD HILLER








FAIRCHILD HILLER

























































FUNCTIONAL SUBSYSTEM AREA 4.0


PROVIDE FOR SERVING OF FOOD
























FUNCTIONAL SUBSYSTEM AREA 5.0


PROVIDE FOR CONSUMPTION OF FOOD



























Conce	pt No. 5. 4. 8	SELECTION RATIONALE		Ţ <u></u>	ctor	**
Title ELECTROSTATIC ATTRACTION (ION SHOWER)			Multiplier	Factor	\[\] Mult x Factor	Chart Use
1	Gravitational Factor	Station G OF Factor OF Factor OF Factor Station G Station G	3	5	15	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	8	24	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 5 	10	1
4	Crew Size Acceptability Factor	The second of th	1	 7 	7	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3		3	1
6	Operability Factor	Reliability X Maintainability 3	1	 3 	3	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	0	0	
8	System Compatibility Factor	High Low High Low High Low Weight X Power 5 X Volume	4	 -5	2	
	FINAL SELECT	TION FACTOR (9.1) = $\frac{\sum (Mult \times Factor)}{Number of Charts Used}$ (9.1)			Sum	Sum
	INTERIM STUDY	SELECTION: DISCARD or STUDY or (> 9)				





SELECTION RATIONALE Concept No. 5. 4. 10 Mult x Factor Select appropriate curve representation, then use corresponding factor. Multiplier Title FELLOW ASTRONAUT * Estimate shape of curve and use the corresponding section number HOLD FOOD Chart into which the curve fails. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. O Factor Concept Effectiveness -(8) 0 **④ ®** 1 Gravitational 12 3 **⑤** Factor 1 Station G Station G Excellent Good 2 Fair Crew 3 0 0 Acceptability Factor 50 1 Crew Acceptability Excellent Factor Good Safety 2 3 0 0 Factor Poor (hazardous) 100% 1 Safety Concept Effectiveness 1009 ூ 0 Ø. Crew Size 1 4 4 (5) Acceptability 1 Factor Crew Number Crew Number -Available or current state-of-the-art Factor Some development required
Broad development required 5 Development 3 8 24 Major development required Risk (1978) or not feasible Factor Development Time, 1 \$, or Complexity Factor 2 х Operability 1 0 0 6 O Factor 1 X Maintainability Reliability -Minimal amount of crew time Factor -Medium 2 6 12 Crew Time 7 - High Factor 1 Min. Max. Crew Time 1.5 1.2 1.0 18.1 System 8 4 33 Compatibility High Low High Low 1 Low High Factor Weight X Power I. 8 X Volume I. S 3 Sum 85 Sum (Mult x Factor) FINAL SELECTION FACTOR (10.6) Number of Charts Used 8 INTERIM STUDY SELECTION: DISCARD


SELECTION RATIONALE Mult x Factor 5.4.11 Concept No. Select appropriate curve representation, then use corresponding factor. Multiplier Title EDIBLE MEMBRANOUS * Estimate shape of curve and use the corresponding section number Factor COATING Chart into which the curve falls, ** Chart use: If chart is used, put 1 in this column; if not used. put in 0. O Factor Concept Effectiveness Ø **④** 30 6 1 Gravitational 3 7 21 (5) Factor 1 Station G Station G Excellent Factor Good 2 Fair Crew 5 15 3 Poor Acceptability Factor 1 Crew Acceptability Excellent Factor Good 3 Safety 2 7 Fair Factor Poor (hazardous) 1 100% Safety Concept Effectiveness 1009 **Ø** Ø, Crew Size 4 1 8 8 (5) Acceptability 1 Factor Crew Number Crew Number -Available or current state -of-the-art Factor Some development required Broad development required
Major development required Development 5 3 5 15 Risk or not feasible (1978)1 Factor Development Time, \$, or Complexity Factor 2 2 X Operability 7.5 7.5 1 6 Factor Complex 1 2.5 X Maintainability Reliability 3 Minimal amount of crew time Factor – Low – Medium 2 7 14 7 Crew Time -High Factor 0 Min. Max. 1 Crew Time Factor 5 8 System 1.2 4.B 4 Compatibility High High High 1 Factor Weight X Power 1.2 X Volume Sum \sum (Mult x Factor) 99.3 Sum FINAL SELECTION FACTOR 12.4 Number of Charts Used 8 YOUTS (e <) INTERIM STUDY SELECTION: DISCARD (≤9)


Concept No.	5. 5. 1	SELECTION RATIONALE			ctor	**
Title OP	EN LIQUID	Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	Mult x Factor	Chart Use
1 G	Factor	The station G Station G Station G Station G	3	0	0	1
2 A	Crew cceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	0	0	1
3	Safety Factor	Excellent Good Fair Poor (hazardous)	2	0	0	1
	Crew Size cceptability Factor	The same of the sa	1	 8 	8	1
5 (Development Risk Factor	Available or current state of the art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 	24	1
6	Operability Factor	X 2 1 1 0 Complex Simple Reliability 3 X Maintainability 3	1	9	9	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	5	10	1
8	System Compatibility Factor	3 1.8 1.5 1.5 2 2 2 1 2 2 2 1 2 2 2 2 2 2 2 2 2 2 2	4	3	12	
	FINAL SELECT	ION FACTOR 8.9 = $\frac{\sum (Mult \times Factor)}{Number of Charts Used}$ 7/			Sum	Sum
	INTERIM STUDY S	ELECTION: DISCARD or STUDY (>9)				


Concept	No. 5.5.2	SELECTION RATIONALE			ğ	**
Title (CONTAINERS	Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used. put in 0.	Multiplier	Factor	Mult x Factor	Chart Use
1	Gravitational Factor	Station G Pactor Station G Station G Station G	3	8	24	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	6	18	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 7 	14	1
4	Crew Size Acceptability Factor	100%	1	 8 	8	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 7 	21	1
6	Operability Factor	3 3 2 2 1 0 Complex Simple Reliability 2 X Maintainability 2	1	4	4	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2]]]	6	1
8	System Compatibility Factor	1.8 1.5 1.0 X 1.0	4	 3 	12	1
	FINAL SELEC	TION FACTOR 13. 4 = \(\sum_{\text{Number of Charts Used}} \) 107			Sum	Sum
	INTERIM STUDY			*		













SELECTION RATIONALE Concept No. 5. 7. 1 Mult x Factor Title NAPKINS (DRY) Select appropriate curve representation, then use corresponding factor. Multiplier * Estimate shape of curve and use the corresponding section number into which the curve falls. Factor Chart 1 ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. O Factor Concept Effectiveness (8) **4 3** 0 6 1 Gravitational 24 3 8 **⑤** Factor 1 Station G Station G Excellent Factor Good Fair 2 Crew 8 3 Poor Acceptability 1 Factor Crew Acceptability Excellent Factor Good 5 3 Safety 2 10 Fair Factor Poor (hazaptous) 100% 1 Safety Concept Effectiveness **®** 1009 0 Ø Crew Size 1 1 1 **(5)** Acceptability Factor Crew Number Crew Number -Available or current state -of-the-art Factor Some development required
Broad development required 5 Development 3 24 -Major development required Risk or not feasible (1978)Factor 1 evelopment Time, \$, or Complexity х Operability 9 6 1 9 Factor Complex 1 X Maintainability Reliability -Minimal amount of crew time Factor - Low -Medium 2 6 12 Crew Time 7 Factor Λ Min. 1 Crew Time 1.8 x System 8 4 0 0 Compatibility High Low Factor Weight X Power X Volume 0 Sum (Mult x Factor) 103 Sum FINAL SELECTION FACTOR 17.2 Number of Charts Used INTERIM STUDY SELECTION: DISCARD


NOTE: THIS SHEET FOR RECORD ONLY, AS THIS CONCEPT IS INCLUDED
AS PART OF SECTION 6.2.

142





NOTE: THIS SHEET IS FOR RECORD ONLY, AS THIS CONCEPT IS NOW PART OF SECTION 6.2.







Concept No. 5 · 7. 5		SELECTION RATIONALE	ctor	**
Title VACUUM CLEANING OF PERSONS & GARMENT		Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls, ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Mult x Factor	Chart Use
l Gravitationa Factor	ı	Station G Station G O Factor	و	1
2 Crew Acceptability Factor		Excellent Good Good Fair Poor Crew Acceptability 3 2	2 6	1
3 Safety Factor		Excellent Good Fair Poor (hazardous) Safety	b 12	1
4 Crew Size Acceptability Factor	,	1 1 2 2 2 5 5 0 Crew Number Crew Number	5 5	1
5 Developmer Risk Factor	nt	Available or current state of the art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	5 15	
6 Operability Factor		3 X 2 1 1 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 2	1
7 Crew Time Factor		Minimal amount of crew time Low Medium High Max. Min. Crew Time	3 6	1
8 System Compatibili Factor	ty	3 1.8 1.5 X 1.0 X Yours	3 1.2	
FINA	. SELECTION FA	ACTOR 6.9 = \(\sum_{\text{Number of Charts Used}} \) = \(\frac{\sum_{\text{(Mult x Factor)}}}{\text{Number of Charts Used}} \) = \(\frac{55.2}{8} \)	Sui	m Sur
INTERIM	STUDY SELECT			












Conce	pt No. 5. 9. 2	SELECTION RATIONALE			ctor	**
Title COCOON OR NET RESTRAINT		Select appropriate curve representation: then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used. put in 0.	Multiplier	Factor	\ \ Mult x Factor	Chart Use
1	Gravitational Factor	Station G Pactor Station G Station G Pactor	3	5	15	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	 4 	12	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 2 	4	1
4	Crew Size Acceptability Factor	100%	1	 8 	8	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 5 	15	1
6	Operability Factor	X 2 Low High Complex Simple Reliability 3 X Maintainability	1	 3 	3	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	 z 	4	
8	System Compatibility Factor	3 1.8 1.5 1.5 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0	4	 2.4 	9.6	1
<u> </u>	FINAL SELEC	TION FACTOR 8.9 = \(\frac{\int (Mult x Factor)}{Number of Charts Used} = \frac{71}{8}			Sum	Sum
	INTERIM STUDY					-








FUNCTIONAL SUBSYSTEM AREA 6.0


PROVIDE FOR CLEAN-UP OF FOOD

















SELECTION RATIONALE Mult x Factor Concept No. 6. 1. 7 Title HAND CLEANING WITH IMPREGNATED DISPOSABLE WIPES Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls, Chart ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. Concept Effectiveness -® **Ø** 4 **©** 1 Gravitational **⑤** 3 8 24 Factor 1 Station G Station G Excellent Factor · Good 2 Crew Fair 3 5 15 Poor Acceptability 1 Factor 100% Crew Acceptability Excellent Good 16 3 Safety 2 8 Fair Factor Poor (hazardous) 1 Safety Concept Effectiveness 1009 1009 0 Ø. 8 Crew Size 8 4 1 ➂ Acceptability 1 Factor Crew Number Crew Number -Available or current state-of-the-art Factor Some development required - Broad development required 5 Development 24 3 8 Major development required Risk or not feasible (1978)1 Factor Development Time, \$, or Complexity x 2 9 1 9 6 Operability **Factor** Complex 1 X Maintainability Reliability -Minimal amount of crew time _Low -Medium 2 2 Crew Time 7 -High 0 Factor Max. Min. 1 Crew Time 1.5 Factor 5 1.2 1.0 12.7 10.8 System 8 Compatibility 1 High High Low High Low Factor Weight .5 X Power 1.8 X Volume .3 Sum \sum (Mult x Factor) 110.8 Sum FINAL SELECTION FACTOR 13.8 Number of Charts Used 8 INTERIM STUDY SELECTION: DISCARD






SELECTION RATIONALE Mult x Factor Concept No. 6.1. 10 Multiplier Select appropriate curve representation, then use corresponding factor. Title GUIDED TRANSPORT * Estimate shape of curve and use the corresponding section number Factor into which the curve falls. Chart | ** Chart use: If chart is used, put 1 in this column; if not used. put in 0. UNIT O Factor Concept Effectiveness **Ø** 4 Gravitational 12 4 3 (5) Factor 1 Station G Station G Factor Good Fair 2 Crew 3 6 18 Acceptability 1 Factor Crew Acceptability Excellent Factor Good 2 6 3 Safety 12 Fair Factor Poor (hazardous) 100% 1 Safety Concept Effectiveness 1009 0 Ø. Crew Size l 8 8 4 **⑤** ั้ Acceptability 1 **Factor** Crew Number Available or current state-of-the-art Factor Some development required - Broad development required Development 5 3 4 12 Major development required Risk or not feasible Factor Development Time, \$, or Complexity 1 3 Factor x 2 2.2 2.2 Operability 6 Factor 1 X Maintainability 1. 5 Reliability 1.5 -Minimal amount of crew time Factor _Low -Medium 2 12 6 Crew Time 7 $\frac{2}{0}$ - High Factor Min. Max. 1 Crew Time 1.5 Factor 5 1.2 System 8 4 .7 2.8 Compatibility Low Low High High Low High Factor 1 Weight X Power X Volume Sum Sum \sum (Mult x Factor) 79 FINAL SELECTION FACTOR Number of Charts Used 8 INTERIM STUDY SELECTION: DISCARD YQUTS (e <)


Conce	ept No. 6. J. 11	SELECTION RATIONALE			ıctor	**
Title CLE	BACK-PACK ANING UNIT	Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used, put in 0.	Multiplier	Factor	\ \ Mult x Factor	Chart Use
1	Gravitational Factor	Factor Station G Station G Factor Station G	3	5	15	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	2	6	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 3 	6	1
4	Crew Size Acceptability Factor	The second secon	1	 8 	8	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 4 	12	1
6	Operability Factor	X 2 1 1 Complex Simple Reliability 1.5 X Maintainability 1.5	1	 _{2.2} 	2.2	1.
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	6	12	1
8	System Compatibility Factor	3 1.8 1.5 1.5 X 1.0 X 1.	4	.7	2.8	1
<u> </u>	FINAL SI	ELECTION FACTOR $8.0 = \frac{\sum (\text{Mult x Factor})}{\text{Number of Charts Used}} = \frac{64}{8}$			Sum	Sum
	INTERIM STU	IDY SELECTION: DISCARD or STUDY				








FAIRCHILD HILLER

SELECTION RATIONALE Concept No. 6. 2. 3 Mult x Factor Select appropriate curve representation, then use corresponding factor. * Estimate shape of curve and use the corresponding section number Title DISPENSER FOR Use Multiplier IMPREGNATED PERSONAL Factor Chart 1 into which the curve falls. CLEASING WIPES ** Chart use: If chart is used, put 1 in this column; if not used. put in 0. O Factor Concept Effectiveness (8) 100% 1009 7 **④ 3**2 **©** 1 Gravitational (5) 3 8 24 Factor 1 Station G Station G Excellent Good Factor 2 Crew Fair 3 8 24 Poor Acceptability Factor 50 100% 1 Crew Acceptability Excellent Factor Good Safety 3 2 8 16 Fair Factor Poor (hazardous) 100% 1 Safety Concept Effectiveness 1000 **@ @** Crew Size 4 1 8 8 (5) Acceptability Factor 1 Crew Number Crew Number -Available or current state -of-the-art Factor Some development required - Broad development required Development 5 3 8 24 Major development required Risk or not feasible (1978)1 Factor Development Time, \$, or Complexity 2 х Operability 6 9 9 **Factor** Complex 1 X Maintainability Reliability 3 -Minimal amount of crew time Factor – Low – Medium 7 Crew Time 10 0 - High Factor Min. Crew Time 3 1.8 1.5 Factor 2 Х System 8 4 2.7 10.3 Compatibility High High Factor 1 Weight .5 X Power I. 8 X Volume 115.8 (Mult x Factor) Sum FINAL SELECTION FACTOR 16.5 Number of Charts Used 7 INTERIM STUDY SELECTION: DISCARD (≤ 9)













NOTE: NO SCORING ASSESSMENT ATTEMPTED












Concept No. 6. 3. 2	SELECTION RATIONALE			tetor	**
Title TEMPORARY DEBRIS COLLECTION STORAGE UNIT	Select appropriate curve representation. then use corresponding factor. * Estimate shape of curve and use the corresponding section number into which the curve falls. ** Chart use: If chart is used, put 1 in this column; if not used. put in 0.	Multiplier	Factor	\[\] Mult x Factor	Chart Use
1 Gravitational Factor	Station G OF Factor Station G Station G Station G	3	8	24	
2 Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	3	6	18	
3 Safety Factor	Excellent Good Fair On 100% Safety	2	6	12	
4 Crew Size Acceptability Factor	The second of th	1	 8 	8	
5 Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Wajor development required or not feasible Development Time, \$, or Complexity	3	8	24	
6 Operability Factor	X 2 1 0 Complex Simple Reliability 3 X Maintainability 3	1	9	9	
7 Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	3	0	
8 System Compatibility Factor	3 1.8 1.5 X 1.0 X	4	3.6	14.4	
FINAL SELECTION FAC	TOR 14.4 = \(\sum_{\text{Norther of Ghorte Used}} \) = \(\sum_{\			Sum	Sı





SELECTION RATIONALE 6.3.4 Mult x Factor Concept No. Title COMBINATION DEBRIS Select appropriate curve representation, then use corresponding factor. Multiplier * Estimate shape of curve and use the corresponding section number into which the curve falls. COLLECTOR | COMPACTOR Chart ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. O Factor Concept Effectiveness **4 3** 7 **©** 1 Gravitational 3 8 24 **(**3) Factor 1 Station G Station G Excellent Factor Good 2 Fair Crew 18 3 6 Poor Acceptability 1 Factor 100% Crew Acceptability Excellent Factor Good 3 Safety 2 6 12 Fair Factor Poor (hazardous) 1 Safety Concept Effectiveness 100 Ø Ø. 4 Crew Size 1 4 (5) Acceptability Factor Crew Number Crew Number Available or current state-of-the-art -Some development required - Broad development required -Major development required 5 Development 3 12 or not feasible Risk 1 Factor Development Time, \$, or Complexity x 2 Factor 3 Operability 1 6 Factor 1 1.5 X Maintainability Reliability -Minimal amount of crew time Factor _Low __Medium 2 8 Crew Time 7 - High Factor Max. Crew Time Min 1 1.5 1.2 1.0 System 8 4 .8 3.2 Compatibility Low High High Low High 1 Factor Weight 1.5 X Power .5 X Volume \sum (Mult x Factor) 84.2 Sum **FINAL SELECTION FACTOR** 10.5 Number of Charts Used 8 INTERIM STUDY SELECTION: DISCARD




NOTE: ADDITIONAL COMPLEXITY FOR SHREDDING IS NOT WARRENTED; COMPACTION ALONE SHOULD SUFFICE.












SELECTION RATIONALE Concept No. 6.3.10 Mult x Factor Select appropriate curve representation, then use corresponding factor. Use Multiplier Title HAND-WASHING SINK Estimate shape of curve and use the corresponding section number into which the curve falls. Factor IN GALLEY Chart ** Chart use: If chart is used, put 1 in this column; if not used, put in 0. Concept Effectiveness 8 **©** Ø 4 l Gravitational **⑤** 3 4 12 Factor 1 Station G Station G Excellent Factor -Good _Fair 2 8 24 3 Crew Poor Acceptability 1 Factor 100% 50 Crew Acceptability Excellent Factor Good 12 Safety 2 6 3 - Fair Poor (hazardous) Factor 1 Safety Concept Effectiveness 1009 1009 Ø Ø, 8 8 Crew Size 1 4 (5) ്ത Acceptability 1 Factor Crew Number Crew Number Available or current state-of-the-art Some development required - Broad development required Development 3 18 -Major development required or not feasible Risk (1978)1 Factor Development Time, \$, or Complexity Factor x 1 1 1 6 Operability 0 Factor Complex 1 X Maintainability Reliability Minimal amount of crew time Low Medium 2 6 12 Crew Time 7 Factor Min. 1 Crew Time Factor 1.2 x 4 | 1.8 7.2 System 8 0 Compatibility High High High Low Factor Weight 1.5 X Power X Volume 1.2 Sum (Mult x Factor) 94.2 Sum FINAL SELECTION FACTOR (11.8) Number of Charts Used 8 INTERIM STUDY SELECTION: STUDY (e <) DISCARD (≤ 9)





Conce	ept No. 6.3. 12	SELECTION RATIONALE		<u> </u>	tor	**
1	HAND DRYING	* Estimate shape of curve and use the corresponding section number	Multiplier	Factor	\ \ Mult x Factor	Chart Use
1	Gravitational Factor	Station G O Factor Station G Station G	3	2	و	1
2	Crew Acceptability Factor	Excellent Good Fair Poor Crew Acceptability	. 3	 	3	1
3	Safety Factor	Excellent Good Fair Poor (hazardous) Safety	2	 4 - 	8	1
4	Crew Size Acceptability Factor	100% 8 10	1	5	5	1
5	Development Risk Factor	Available or current state-of-the-art Some development required Broad development required Major development required or not feasible Development Time, \$, or Complexity	3	 8 	24	1
6	Operability Factor	Reliability 3 X Maintainability 3	1	ا و -	9	1
7	Crew Time Factor	Minimal amount of crew time Low Medium High Max. Min. Crew Time	2	 0 	0	2
8	System Compatibility Factor	High Low High Low High Low Weight X Power X Volume	4	3.6	14.4	£
	FINAL SELEC	TION FACTOR $(B.7)$ = $\frac{\sum_{\text{Number of Charts Used}}}{\text{Number of Charts Used}}$ $(B.7)$			Sum	Sum
	INTERIM STUDY	SELECTION: DISCARD or STUDY				

MAY BE NECESSARY TO DRY UTENSILS BY HAND UNDER CERTAIN COMPELLING
CONDITIONS; THEREFORE RETAIN FOR STUDY, OVERRIDING SELECTION RATIONALE SCORE









FUNCTIONAL SUBSYSTEM AREA 7.0

PROVIDE FOR RECORDING OF FOOD

No selection rationale sheets were prepared for this functional subsystem area. Requirements are presented in Final Report, Volume I, Section III, paragraph 7.0.